



7001LT 70-inch

Touchscreen Signage



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The 7001LT 69.5-inch Interactive Digital Signage display combines an infrared touchscreen with a professional grade, large format display in a slim, integrated package. With a total thickness of 3.7 inches (94mm), the 7001LT is compliant with the ADA requirement of less than 4" protrusion for wall mounted products when used with a compatible wall-mount.

With a 700 nit LED panel, the 7001LT is a bright, high quality display suitable for public environments. The infrared touchscreen enables up to 20 simultaneous touches for multi-user interaction. This touch technology offers a fast and extremely sensitive response similar to the experience on mobile devices and is compatible with Windows® 7, Windows 8.1 and Windows 10 operating systems. The touchscreen is 4mm thick with fully tempered glass. The 7001LT smart video sensing technology automatically detects new video sources and automatically switches to them.

Thin (<4" mounted) design is attractive and compliant with ADA and IBC protrusion requirements

Reliable, integrated IDS solution with optional NFC / RFID scanners and webcam kits

Remote management capability for device hardware with support for future cloud applications

7001LT 70" Touchscreen Signage

Specifications	
Model	7001LT
Form Factor	Interactive Digital Signage
Bezel Color	Black
Active Display Area (W x H)	60.6" x 34.1" (1538.9mm x 865.6mm)
Dimensions* (W x D x H)	62.9" x 3.7" x 36.4" (1600mm x 94mm x 925 mm)
Display Technology	Active matrix TFT LCD with LED backlight, 16.7 million colors, 8 ms response time (tr+tf)
Mounting Options	VESA 4-hole mount per MIS-F, 600, 600, 8MM Optional thin, tilting wall mount E248743 available to ensure ADA and IBC compliance
Diagonal Size	69.5" (176.6cm)
Native Resolution	1920x1080 60Hz (Full HD), 16:9 aspect ratio; Other resolutions supported.
Brightness (typical)	LCD Panel: 700 nits; with Infrared: 630 nits
Number of Touches	up to 20 touches
Viewing Angle (typical)	Horizontal: ±88°, 176° total; Vertical: ±88°, 176° total
Contrast Ratio (typical)	5000:1
Video Inputs	Analog VGA on Female DE-15 connector; HDCP-capable HDMI 1.3 on Type A connector; DisplayPort 1.1a connector; Input Video Horizontal Sync frequency range: 53-70KHz; Input Video Vertical Sync (frame rate) frequency range: 47-63Hz
Input Power Connector	IEC 60320 C14
Power Consumption (typical)	Monitor Only : 110V at 60Hz, ON: 203.13W, SLEEP: 10.75W, OFF: 1.47W; 230V at 50Hz, ON: 198.01W, SLEEP: 9.77W, OFF: 1.6W
Audio	Internal Speakers: 4 x 5W stereo speakers to allow Stereo configuration in portrait and landscape mode. Input audio connector: 3.5mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5mm TRS jack
Weight	Unpackaged, monitor only: 149.5 lb (67.8kg)
Shipping Dimensions (W x D x H)	70.6" x 15.2" x 45.2" (1794mm x 386mm x 1149mm)
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory approvals and declarations	UL, FCC; cUL, IC; CB; CE; VCCI; C-Tick; NOM CoC; GOST; BSMI; KC; e-Standby; CCC, China RoHS With RFID: UL, FCC; CE
Accessories	MSR (E545781), NFC Adapter (E918074), OPS Kit (E102270), Replacement OSD Controller (E483757) Replacement Cable Kit (E000263), Wall Mount Kit (E248743), Webcam (E688656)
Warranty	3 years standard. On-site exchange (U.S. only) and extended warranty available
MTBF	50,000 hours demonstrated
What's in the box	7001LT, OSD Remote, QIG, Japanese Class A Kiosk Info, User Manuals and Driver CD, HDMI cable (Type A plug to Type A plug), VGA + RS232 Y-Cable, VGA Cable, USB cable (Type A plug to Type B plug), power cable, NA plug, EU/KR plug UK plug, AR plug, CH plug, JP plug, 3-pin to 2-pin adapter for JP power cable

Ordering Information

Model	Part Number	Touch Technology	Color	Availability
7001LT	E183504	Infrared (up to 20 touches)	Black	Worldwide

Optional Computer Modules

Model	Part Numbers (ECMG2B - for IDS 01 Series Displays)	Processor	RAM	Storage	OS
ECMG2-i3	E001292	Intel Core i3 3.4GHz HD4400	2GB	320GB HDD	No OS
	E001293	Intel Core i3 3.4GHz HD4400	2GB	320GB HDD	Windows 7
	E001294	Intel Core i3 3.4GHz HD4400	2GB	320GB HDD	Windows 8.1 Embedded
	E991018	Intel Core i3 3.4GHz HD4400	2GB	128GB SSD	Windows 10
ECMG2-i5	E001295	Intel Core i5 3.7GHz HD4600	4GB	320GB HDD	No OS
	E001296	Intel Core i5 3.7GHz HD4600	4GB	320GB HDD	Windows 7
	E001297	Intel Core i5 3.7GHz HD4600	4GB	320GB HDD	Windows 8.1 Embedded
	E991722	Intel Core i5 3.7GHz HD4600	4GB	128GB SSD	Windows 10
ECMG2-i7	E001298	Intel Core i7 4.0GHz HD4600	8GB	320GB HDD	No OS
	E001299	Intel Core i7 4.0GHz HD4600	8GB	320GB HDD	Windows 7
	E001300	Intel Core i7 4.0GHz HD4600	8GB	320GB HDD	Windows 8.1 Embedded
	E992193	Intel Core i7 4.0GHz HD4600	8GB	128GB SSD	Windows 10

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2016 Elo Touch Solutions, Inc. All rights reserved. 16113AES00044

