



**10.4" Rimless POS LCD Monitor**



New Capacitive Touch keys control design provide high durability of operation, also with a thin & whole flat front panel gives an elegant and compact appearance.

**Features**

1. Rimless front bezel design, spill & dust proof, meets IP54 requirement
2. Low power consumption only 6W with LED backlight
3. Cable cover to prevent unexpected pull from users
4. Sleek surface throughout monitor's appearance
5. Viewing angle adjustment up to 68°
6. Universal power brick with changeable plug
7. VESA 75 x 75 mm wall mounting standard
8. User friendly OSD control buttons
9. Integrated protection glass (**P104VG**)  
or 5 wires Resistive touch (**P104VR**)
10. Smart cable management
11. Small footprint



**Specification**

Model	P104VG / P104VR
Cabinet Color	Black or White
Cover Lens	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% ( <b>P104VG</b> ) 5 wires Resistive touch ( <b>P104VR</b> )
Display Type	10.4" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600
Brightness	300 cd/m <sup>2</sup> (typ.)
Contrast Ratio	500:1 (typ.)
Viewing Angle	110° (H) / 150° (V)
I/O Connectivity	mini VGA 14 pins, DC 12V, Mini USB (for P104VR only)

\* Specification is subject to be changed without prior notice.

**Application**


Supermarket / Chain stores / Hospitality /  
Factory automation

**Universal power plug**




**I/O indication**

**P104VG**



**P104VR**



**Dimension (unit: mm)**

